



# Safety Data Sheet acc. to OSHA HCS

Printing date 05/01/2018 Reviewed on 04/30/2018

#### 1 Identification

#### - Product identifier

- Trade name: Max 5000 Epoxy

- Synonyms: Max 5000 Aluminum Bonder - Part A - Resin

- Part number: MAX5000A

- Application of the substance / the mixture Adhesives

#### - Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Plastech-Weld 41871 Mitchell Rd. Novi, MI 48377 USA

Telephone: +1-313-963-3194 Email: plastechweld@gmail.com Website: www.plastechweld.com

- Information department: Product safety department
- Emergency telephone number: United States: 1-800-424-9300

International: +1-703-527-3887

#### 2 Hazard(s) identification

#### - Classification of the substance or mixture



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

#### Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
  - Hazard pictograms



GHS07

- Signal word Warning
- Hazard-determining components of labeling:

Bisphenol-A epoxy resin

Bisphenol F epoxy resin

# - Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

# - Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash face, hands and any exposed skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves.

P280 Wear eye protection / face protection. P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

# Safety Data Sheet acc. to OSHA HCS

Reviewed on 04/30/2018 Printing date 05/01/2018

# Trade name: Max 5000 Epoxy

(Contd. of page 1)

P321 Specific treatment (see on this label).

P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### - Classification system:

NFPA ratings (scale 0 - 4)



#### - HMIS-ratings (scale 0 - 4)



#### - Other hazards

- Results of PBT and vPvB assessment
  - PBT: Not applicable.
  - vPvB: Not applicable.

### 3 Composition/information on ingredients

- Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

- Dange	rous components:	
25068-38-6	Bisphenol-A epoxy resin	60 - 69%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
	Bisphenol F epoxy resin	30 - 39%
	Skin Irrit. 2, H315; Skin Sens. 1, H317	
	Synthetic amorphous silica (fumed)	1 – 4%
	Combustible Dust	

#### 4 First-aid measures

#### - Description of first aid measures

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
  - Most important symptoms and effects, both acute and delayed No further relevant information available.
  - Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

- Extinguishing media
  - Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
  - Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

#### 6 Accidental release measures

# - Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

#### - Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/01/2018 Reviewed on 04/30/2018

Trade name: Max 5000 Epoxy

(Contd. of page 2)

#### - Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

#### - Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

#### - Handling:

### - Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
  - Storage:
    - Requirements to be met by storerooms and receptacles: No special requirements.
    - Information about storage in one common storage facility: Not required.
    - Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters
  - Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the creation were used as basis.

#### Exposure controls

- Personal protective equipment:
  - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### - Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### - Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR

- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/01/2018 Reviewed on 04/30/2018

Trade name: Max 5000 Epoxy

(Contd. of page 3)

9 Physical and chemical properties	
- Information on basic physical and che - General Information - Appearance: - Form: - Color: - Odor:	emical properties  Viscous  Whitish  Characteristic
- Odor threshold:	Not determined.
- pH-value:	Not determined.
<ul> <li>Change in condition</li> <li>Melting point/Melting range:</li> <li>Boiling point/Boiling range:</li> </ul>	Undetermined. > 200 °C (> 392 °F)
- Flash point:	95 °C (203 °F)
- Flammability (solid, gaseous):	Not applicable.
- Decomposition temperature:	Not determined.
- Auto igniting:	Product is not selfigniting.
- Danger of explosion:	Product does not present an explosion hazard.
- Explosion limits: - Lower: - Upper:	Not determined. Not determined.
- Vapor pressure:	Not determined.
- Density: - Relative density - Vapor density - Evaporation rate	Not determined. Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with</li> <li>Water:</li> </ul>	Not miscible or difficult to mix.
- Partition coefficient (n-octanol/wa	ter): Not determined.
- Viscosity: - Dynamic at 20 ℃ (68 ℉): - Kinematic:	65,000 mPas Not determined.
- Solvent content: - VOC content:	0.00 % 0.0 g/l / 0.00 lb/gl
- Solids content: - Other information	1.5 % No further relevant information available.

# 10 Stability and reactivity

- Reactivity No further relevant information available.
  - Chemical stability
    - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- Information on toxicological effects
  - Acute toxicity:
    - Primary irritant effect:
      - on the skin: Irritant to skin and mucous membranes.
      - on the eye: Irritating effect.
    - Sensitization: Sensitization possible through skin contact.
  - Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

# Safety Data Sheet acc. to OSHA HCS

Printing date 05/01/2018 Reviewed on 04/30/2018

Trade name: Max 5000 Epoxy

(Contd. of page 4)

Irritant

- Carcinogenic categories
  - IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

- NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# 12 Ecological information

- Toxicity
  - Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
  - Bioaccumulative potential No further relevant information available.
  - Mobility in soil No further relevant information available.
- Ecotoxical effects:
  - Remark: Toxic for fish
- Additional ecological information:
  - General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- Results of PBT and vPvB assessment
  - PBT: Not applicable.
  - vPvB: Not applicable.
- Other adverse effects No further relevant information available.

# 13 Disposal considerations

- Waste treatment methods
  - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
  - Recommendation: Disposal must be made according to official regulations.

14 Transport information		
- UN-Number - DOT, ADN, IMDG, IATA	not regulated	
- UN proper shipping name - DOT, ADN, IMDG, IATA	not regulated	
- Transport hazard class(es)		
- DOT, ADN, IMDG, IATA - Class	not regulated	
- Packing group - DOT, IMDG, IATA	not regulated	
- Environmental hazards: - Marine pollutant:	Yes	
- Special precautions for user - Stowage Category	Not applicable. A	
- Transport in bulk according to Annex II of	MARPOL73/78	
and the IBC Code	Not applicable.	
- UN "Model Regulation":	not regulated	entd on page 6)

(Contd. on page 6)

# Safety Data Sheet acc. to OSHA HCS

Reviewed on 04/30/2018 Printing date 05/01/2018

Trade name: Max 5000 Epoxy

(Contd. of page 5)

# 15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65

Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories

EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Contact: Safety, Health and Environmental Affaires
  - Date of preparation / last revision 05/01/2018 / 18
  - Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- \* Data compared to the previous version altered.

The information set forth is based on information that Plastech-Weld Inc. believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and Plastech-Weld Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.